

Crush proof flexible hose with fittings



Crush-proof flexible hose with rubber fittings;

Ideal for the suction of all dust, debris and abrasive materials. With hard rubber cuffs. Surface inside quite smooth, excellent flexibility, color black.

Pressure resistance: 500 mbar

Temperature range: -30C° +60C°

FXC407 – Complete flexible hose with fittings; 40mm - 7,5 meter

FXC507 – Complete flexible hose with fittings; 50mm - 7,5 meter

FXC410 – Complete flexible hose with fittings; 40mm - 10 meter

FXC510 – Complete flexible hose with fittings; 50mm - 10 meter

FXA407 – Complete flexible hose with fittings conductive; 40mm 7,5m

FXA507 – Complete flexible hose with fittings conductive; 50mm 7,5m

FXA410 – Complete flexible hose with fittings conductive; 40mm 10m

FXA510 – Complete flexible hose with fittings conductive; 50mm 10m



Crush proof flexible hose



Crush-proof flexible hose

Ideal for the suction of all dust, debris and abrasive materials. With hard rubber cuffs. Surface inside quite smooth, excellent flexibility, color black.

Pressure resistance: 500 mbar

Temperature range: -30C° +60C°

FXC401 – Flexible hose 40mm - the meter

FXC501 – Flexible hose 50mm - the meter

FXA401 – Flexible hose conductive 40mm - the meter

FXA501 – Flexible hose conductive 50mm - the meter



Rubber fitting



Rubber Fitting

In durable rubber, mounted on the suction hose.

Total length: 110mm

Weight: 90g

ARF030 – Ø 32mm

ARF040 – Ø 40mm

ARF050 – Ø 50mm

ARF041 – 360° revolving rubber cuff Ø 40mm

ARF031 – Ø 32mm conductive

ARF041 – Ø 40mm conductive

ARF051 – Ø 50mm conductive



Metal fitting



Metal Fitting

In metal, mounted between the rubber fitting and the tools
ARC, AST, ACC.

Total length: 130mm

Weight: 80g

AMF030 – Ø 32mm

AMF040 – Ø 40mm

AMF050 – Ø 50mm



Metal coupling for metal inlet valve MEV050



Metal Coupling

Used to connect the metal inlet valve MEV050 with the flexible hose. Made of zinc coated steel.

Total length: 200mm

Weight: 150g

AMC030 – Ø 32mm

AMC040 – Ø 40mm

AMC050 – Ø 50mm

S – shaped connection wand Premium



S – shaped Wand Premium

Professional chromate steel or aluminum S-shaped handle fitted with a quick coupling.

Used to connect the suction hose with a floor brush.

Total height: 95cm

Weight: 1.750g

ASW040 – chromate steel Ø 40mm

ASW050 – chromate steel Ø 50mm

ASW041 – Aluminium Ø 40mm

ASW051 – Aluminium Ø 50mm

S – shaped connection wand Standard



S – shaped Wand Standard

Chromate steel tube S-shaped handle fitted.

Used to connect the suction hose with a floor brush.

Total height 93cm.

Weight: 1.250g

ASW041 - Ø 40mm

ASW051 - Ø 50mm

Technical floor brush Premium



Floor Brush Premium

Steel floor brush with adjustable wheels, for industrial dust & debris on technical floors. With rubber casing to prevent damage to the brush and to the furniture.

With a quick fix coupling.

Brush width: 400mm

Attachment diameter: Ø 40mm

Weight: 460g

AFB440 – 400mm / Ø 40mm

AFB450 – 400mm / Ø 50mm

Tecnical floor brush Standard



Floor Brush Standard

Ideal for industrial dust & debris on technical floors.
Light weight.

Brush width: 400mm
Attachment diameter: Ø 40mm
Weight: 340g

AFB441 – 400mm / Ø 40mm

AFB451 – 400mm / Ø 50mm

Rubber cone with end cutted 45°



Rubber Cone

For suction of chips hand cleaning on machines. Made of a special high resistance rubber. The all-rounder cleaning tool. Made of special conductive antistatic rubber.

Cone length: 200mm
Weight: 140g

ARC040 - Ø 40mm

ARC050 - Ø 50mm

To be used with AMF040 / AMF050.

Round dusting brush with 90° bend



Round Brush

With polyester hair. For delicate surfaces and persistent dust. With zinc coated steel bend.

Brush diameter: 100mm
Weight: 260g

ARB040 - Ø 40mm

ARB050 - Ø 50mm

Flat crevice tool



Crevice Tool

In hard rubber, for all kind of surfaces, specially designed to clean areas difficult to reach.

Made of special conductive antistatic rubber.

Total length: 300mm
Weight: 180g

ACT040 - Ø 40mm

ACT050 - Ø 50mm

Crevice tool Metal



Crevice Tool

Available in zinc coated steel or in stainless steel.
Designed to clean surfaces which are difficult to reach.

Total length: 300mm

Weight: 190g

ACT041 – zinc coated steel Ø 40mm

ACT051 – zinc coated steel Ø 50mm

ACT042 – stainless steel Ø 40mm

ACT052 – stainless steel Ø 50mm

Scraping tool



Scraping Tool

In rubber, for all kind of surfaces, specially designed to clean persistent dust and wet surfaces.

Made of special conductive antistatic rubber.

Total length: 175mm

Inlet width: 125mm

Weight: 120g

AST040 - Ø 40mm

AST050 - Ø 50mm

To be used with AMF040 / AMF050.

Curved cone tool



Curved Cone

For suction of small chips in extremely hard to reach areas.

Made of a special high resistance rubber.

Made of special conductive antistatic rubber.

Cone length: 300mm

Weight: 170g

ACC040 - Ø 40mm

ACC050 - Ø 50mm

To be used with AMF040 / AMF050.

Suction lance



Suction lance

For suction of small chips and granulate in extremely hard to reach areas. Available in stainless steel and aluminium.

Lance length: 1000mm

Weight: 3250g

ASL040 – aluminium Ø 40mm

ASL050 – aluminium Ø 50mm

ASL041 – stainless steel Ø 40mm

ASL051 – stainless steel Ø 50mm